

## PHASE AND MOTOR ROTATION TESTER



**CAT III  
600V**

### Part No. T860

A multi-purpose three phase tester that has the additional feature of checking motor rotation. When the armature is turned the phase rotation will be indicated. Ideal for determining which phase sequence when connecting a three phase motor to the supply and ensuring the correct rotation.

- Indicates motor rotation
- Phase and open phase indication
- Plug-in leads
- CAT III 500V
- Easy to use
- Electronic circuits
- No mechanical parts

EA QTY 1

<b>Compliance and Safety</b>	EN61010 CAT III 500V
<b>Contents</b>	The T860 comes in a gift box with soft vinyl case, crocodile clips on plug-in leads, and instruction manual.
<b>Dimensions</b>	L153 x W72 x T35mm
<b>Batteries</b>	1 x 9V 6F22 installed
<b>Weight</b>	182g with batteries
<b>Replacement Test Leads</b>	AL30RYBKIT

Feature	Range
Input Voltage	100 to 600V AC
Frequency	45 to 480Hz
Power Consumption Motor Rotation	±14mA
Power Consumption Phase Rotation	±7mA

## PHASE ROTATION INDICATOR WITH FUSED HEADS



**CAT IV  
600V**

### Part No. T855

The T855 is suitable for line workers to check phase sequence on aerial electrical conductors. The long leads can easily reach across the phases and are fused for increased protection. The probes have pluggable crocodile clips for easy attachment to bare conductor.

- Live line indication
- Push button for motor rotation testing
- Heavy duty crocodile clips
- Test probes fused for extra protection, shrouded tips
- CAT IV 600V
- Phase sequence - clockwise rotation correct
- Long leads for overhead lines

EA QTY 1

<b>Compliance and Safety</b>	EN61010 CAT IV 600V, CE
<b>Contents</b>	The T855 comes in a gift box with soft vinyl case, crocodile clips on built-in colour coded leads, and instruction manual.
<b>Dimensions</b>	L134 x W85 x T45mm
<b>Batteries</b>	None
<b>Weight</b>	530g with test leads

Feature	Range
Input Voltage	200 to 600V AC
Frequency Range	50 to 60Hz
Operating Temp.	-10 to 40°C @ 80% RH
Fuses	0, 5A x 3 HRC