

LED DIMMABLE CANDLE GLOBES

Product Features

- Input voltage 240V AC 50/60Hz
- Wattage: 4W
- 18pcs EDISON 3014 LED chips
- Life time: 30,000HRS
- CRI: 80
- Beam angle: 300°
- Aluminium cap base & heatsink
- Clear or frosted glass lamp cover
- Ambient temperature: -20~45°C
- **Suitable for dimming**
- **Recommended trailing edge dimmers**
- Can work with sensor
- Carton QTY: 1/10/100
- **3 year replacement warranty**

DIMMABLE!



clear cover

frosted cover

RECOMMENDED DIMMERS:

1. HPM Legrand Trailing Edge CAT 400T (Min 3 lamps; Max 15 globes per dimmer)
2. Clipsal Trailing Edge 450TM (Min 3 lamps; Max 16 globes per dimmer)
3. Clipsal Universal 32E450UDM (Min 3 lamps; Max 16 globes per dimmer)
4. Clipsal Universal 31E2RUDM 350 (Min 3 lamps; Max 13 globes per dimmer)
5. Luxman Trailing Edge T400PCFL (Min 3 lamps; Max 15 globes per dimmer)
6. CLA LYNX 400VA Trailing Edge (Min 2 lamps; Max 15 globes per dimmer)

CODE	DESCRIPTION	BASE	WATT	KELVIN	LUMENS	LENGTH	DIAM.
CLEAR							
LEDCC14-4-30	18PCS LED CANDLE CLEAR SES 3000K	E14	4=25W	3000K	290LM	125MM	Ø35MM
LEDCC15-4-30	18PCS LED CANDLE CLEAR SBC 3000K	B15	4=25W	3000K	290LM	124MM	Ø35MM
LEDCC14-4-50	18PCS LED CANDLE CLEAR SES 5000K	E14	4=25W	5000K	310LM	125MM	Ø35MM
LEDCC15-4-50	18PCS LED CANDLE CLEAR SBC 5000K	B15	4=25W	5000K	310LM	124MM	Ø35MM
FROSTED							
LED CF14-4-30	18PCS LED CANDLE FROSTED SES 3000K	E14	4=25W	3000K	275LM	125MM	Ø35MM
LED CF15-4-30	18PCS LED CANDLE FROSTED SBC 3000K	B15	4=25W	3000K	275LM	124MM	Ø35MM
LED CF14-4-50	18PCS LED CANDLE FROSTED SES 5000K	E14	4=25W	5000K	295LM	125MM	Ø35MM
LED CF15-4-50	18PCS LED CANDLE FROSTED SBC 5000K	B15	4=25W	5000K	295LM	124MM	Ø35MM